

CL400



GAS PREP

- ▶ 912978 O2 assist gas regulator:
 - ▶▶ Dome loaded regulator.
 - ▶▶ Adjustable to 500PSI
 - ▶▶ CGA540
 - ▶▶ ½" ports
 - ▶▶ Max flow 6000 SCFH
- ▶ 913038 N2 regulator:
 - ▶▶ Dome loaded regulator.
 - ▶▶ Adjustable to 500PSI
 - ▶▶ CGA540
 - ▶▶ ½" ports
 - ▶▶ Max flow 6000 SCFH
- ▶ Qty. (2) each 922670 25ft, or 922671 50ft, or 922672 75ft assist gas hoses. **MUST be Blue Synflex Moisture-Lok**
- ▶ Qty. (2) ea. 914664 Regulator for He and N2 :
 - ▶▶ Dome loaded regulator
 - ▶▶ Adjustable to 100PSI
 - ▶▶ CGA580
 - ▶▶ Inlet max pressure 3000PSI
 - ▶▶ Max delivery 100PSI
 - ▶▶ M6 Tube Fitting outlet
- ▶ 914665 Regulator for CO2:
 - ▶▶ Dome loaded regulator
 - ▶▶ Adjustable to 100PSI
 - ▶▶ CGA320
 - ▶▶ Inlet max pressure 3000PSI
 - ▶▶ Max delivery 100PSI
 - ▶▶ M6 Tube Fitting outlet

CHEMICAL PREP

- ▶ 909480 Dowtherm
 - ▶▶ Qty. 40 Gallons
 - ▶▶ **Customer must supply distilled water (60 gallons)**
- ▶ 907125 Optics Cleaning Kit
- ▶ Qty. (2) 921695 Drive axis lubrication grease:
 - ▶▶ ISOFLEX NCA 15 400 GRAM