



PLA Material Safety Data Sheet

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PLA 3D Printing Filament

PRODUCT IDENTIFICATION: PLA x/y (x denotes diameter, y denotes color)

SYNONYMS: PLA, Co-Polyester, Polylactic Acid, Polylactide

MANUFACTURED / IMPORTED BY: TAW Global, LLC

DIVISION: Quantum3D

ADDRESS: 8135 Cox's Dr Suite 208, Portage, MI 49002

SOLD BY: New Valence Robotics Corporation

ADDRESS: 12 Channel St Suite 601, Boston, MA 02210

PHONE: 857-529-6397

WEBSITE: <https://nvbots.com/>

CHEMTREC PHONE: 800-424-9300

CHEMICAL NAME: Polylactic Acid

CHEMICAL FAMILY: Polyester

CHEMICAL FORMULA: (C₃H₄O₂)_n

PRODUCT USE: Used for generating models using a 3D printer

PREPARED BY: Arjun Chandar, Director of Operations, New Valence Robotics Corporation

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT AND CAS NO.	% WEIGHT	OSHA EXPOSURE LIMITS	ACGIH EXPOSURE LIMITS
Polylactic Acid (26100-51-6)	>90%	None	None
N.N Ethylene bistearamide (110-30-5)	<5%	None	None
Typical Antioxidant	<5%	None	None
Typical Pigment	<5%	None	None



SECTION 3: HAZARDS IDENTIFICATION

HAZARD STATEMENT: NONE
PRECAUTIONARY STATEMENT: NONE
SIGNAL WORD: NONE
PICTOGRAM: NONE

POTENTIAL HEALTH EFFECTS

EYES: Solid or dust may cause irritation or corneal injury due to mechanical action

SKIN: May cause slight skin irritation, but essentially nonirritating except for mechanical injury

INGESTION: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

INHALATION: Inhalation of dust may cause shortness of breath, a sore throat and cough. Considered a low hazard under normal industrial or commercial handling.

SECTION 4: FIRST AID MEASURES

EYES: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.

SKIN: Rinse immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician. Cool skin immediately with cold water after contact with hot polymer.

INGESTION: Drink water as a precaution. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Call a physician immediately.

INHALATION: Move to fresh air. Call a physician immediately.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Treat symptomatically.



SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR

UPPER: N/A

LOWER: N/A

AUTOIGNITION TEMPERATURE:

F: 730

C: 388

NFPA HAZARD CLASSIFICATION

HEALTH: 0

FLAMMABILITY: 1

REACTIVITY: 0

OTHER:

EXTINGUISHING MEDIA: Foam, Water, Carbon dioxide (CO₂), Dry chemical, Alcohol resistant foams are preferred if available. General-purpose synthetic foams (including AFFF) or protein foams may function, but much less effectively.

SPECIAL FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Use personal protective equipment. See Section 9. Remove all sources of ignition.

Avoid dust formation. Avoid contact with skin and eyes. Sweep up to prevent slipping hazard.

ENVIRONMENTAL PRECAUTIONS: Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

METHODS FOR CLEANING UP: Shovel into suitable container for disposal.



SECTION 7: HANDLING AND STORAGE

SAFE HANDLING ADVICE: Avoid contact with skin and eyes. Avoid dust formation. Workers should be protected from the possibility of contact with molten material during fabrication. Considered low hazard under normal industrial or commercial handling. Use personal protective equipment.

STORAGE: Store in cool place. Keep at temperatures below 60 °C. No special restrictions on storage with other products.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES: Where possible, use exhaust ventilation and good general extraction. Provide appropriate exhaust ventilation at places where dust is formed.

EXPOSURE LIMITS: None established. This material can generate Particulates Not Otherwise Classifiable (PNOC). The Occupational Safety and Health Administration (OSHA) PEL/TWA for PNOC is 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction. The American Conference of Governmental Industrial Hygienists (ACGIH) TLV/TWA for PNOC is 10 mg/m³ for inhalable particulates and 3 mg/m³ for respirable particulates.

CONTROL PARAMETERS: None

EYE PROTECTION: Safety glasses with side-shields, goggles.

SKIN AND BODY PROTECTION: Impervious clothing.



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, translucent, opaque

ODOR: Sweet

PHYSICAL STATE: Solid

pH AS SUPPLIED: N/A

BOILING POINT: N/A

MELTING POINT:

F: 302 to 320

C: 150 to 160

GLASS TRANSITION TEMPERATURE:

F: 131 to 140

C: 55 to 60

DECOMPOSITION TEMPERATURE:

F: 446

C: 230

VAPOR PRESSURE (mmHg): Not determined

VAPOR DENSITY (AIR = 1): Not determined

SPECIFIC GRAVITY (H₂O = 1): 1.25 g/cc

EVAPORATION RATE: Not determined

WATER SOLUBILITY: Insoluble



SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under recommended storage conditions.

REACTIVITY: None expected under conditions of normal use.

CONDITIONS TO AVOID: Temperatures above 446F (230 °C). Avoid keeping resin molten for excessive periods of time at elevated temperatures. Prolonged exposure will cause polymer degradation.

MATERIALS TO AVOID: Oxidizing agents, strong bases.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Burning produces obnoxious and toxic fumes - aldehydes, carbon monoxide (CO), carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

PRINCIPLE ROUTES OF EXPOSURE: Eye contact, Skin contact, Inhalation, Ingestion.

ACUTE TOXICITY: None noted during use.

LOCAL EFFECTS: Product dust may be irritating to eyes, skin and respiratory system. Particles, like other inert materials, are mechanically irritating to eyes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SPECIFIC EFFECTS: May cause skin irritation and/or dermatitis. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough. Burning produces irritant fumes.

CHRONIC TOXICITY: None noted during use.

REPRODUCTIVE TOXICITY: No data is available on the product itself.

CARCINOGENIC EFFECTS: None of the components of this product are listed as carcinogens by IARC, NTP, or OSHA.



SECTION 12: ECOLOGICAL INFORMATION

SHIPPING CONTAINERS: Cardboard boxes containing sealed plastic pouches with filament spools. Desiccant included in sealed pouches.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: In accordance with local and national regulations.

SECTION 14: TRANSPORT INFORMATION

D.O.T.: Not regulated as hazardous.

The information in this MSDS/SDS was obtained from sources which we believe are reliable.

However, the information is provided without any warranty, express or implied, regarding its correctness.

The conditions or methods of handing, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS/SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS/SDS information may be applicable.